



THE STANDARD IN ENGINEERING EXCELLENCE



11 Brandywine Dr, Deer Park, NY 11729 - Ph: (631) 586-9525 Fx: (631) 586-2599 Em: info@unorthodoxracing.com

**Thank you and congratulations on your purchase of the finest performance products available today.**

**We appreciate your feedback, good or bad, about the quality and performance of this product.**

**Our goal is 100% customer satisfaction and your feedback is very important in achieving this goal!**

- This pulley kit Part# 02101170\_ contains a crank pulley: underdrive stock belt layout (Ultra S) Part# 0210117. Check that the part number matches the number engraved on the back of the pulley. If the part numbers or quantity of parts do not match, do not install them and call the dealer you purchased the parts from or call our tech line direct.

### **Other Fine Unorthodox Racing Products Available For Your Vehicle**

- Aluminum flywheel (Ultra L) Part# 06.10.117.00. (S13 / S14)
- Performance clutch kits (Ultra G) available for all models, kits include pressure plate, disc, required bearings and an alignment tool.
  - Full faced Kevlar disc holds 30% more power than the stock clutch (Solid or sprung hub disc). (Street Sport) For stock to slightly modified cars.
  - Windowed Kevlar disc holds 45% more power than the stock clutch (Solid or sprung hub disc). (Sport Mod) For slightly to moderately modified cars.
  - Four or Six (6) paddle Ceramic disc holds 80% or Feramic discs holds 110% more power than the stock clutch (Solid or sprung hub disc). Ceramic (Sport Pro) for moderately to heavily modified cars and Feramic (Race Pro) is designed for heavily to race modified cars.

### **Installation Instructions**

#### **Nissan S13 / S14 SR20DET RWD 2.0L DOHC 16V Turbo**

- **Notice:** These instructions are not a replacement for the factory manual; factory specified tools maybe required for removal of the original parts.
- Open the hood to gain access to the engine compartment.
- Raise the vehicle and place safety / jack stands on passenger and driver side frame rails for access underneath the vehicle.
- Remove the under body engine compartment shroud.
- Unbolt and remove the fan from the water pump, leave fan inside shroud assembly.
- Loosen the crankshaft pulley bolt but do not remove yet.
  - Manual Transmission: Have helper put car in 5th gear and hold the brake pedal firmly, the bolt is very tight and will require significant force to loosen.
  - Automatic transmission: Follow the crank pulley removal procedure/s specified in the factory manual.
- Loosen the alternator and water pump belt and remove them.
- Loosen the air conditioning idler pulley nut then loosen the air conditioning belt and remove.
- Loosen and remove all the remaining accessory belts and remove the original crankshaft pulley.
- **The pulley comes with a 1MM thick steel sleeve pressed over the outer diameter of the hub on the rear of the pulley, side of the pulley with part #'s, where the pulley fits into the engine oil seal. For visual reference the sleeve has a slight taper at the end. The front oil seal rides against this sleeve sealing the crankcase. As a precaution check to insure the pulley has the sleeve pre-installed. Do not install if sleeve is not present as a major oil leak or serious engine damage could occur.**
- Install the new underdrive pulley, lightly coat the inner bore of the new pulley with anti-seize compound and tighten the crankshaft pulley bolt, see torque specification below. - Make sure that the crank snout edge has no burrs, if no burrs are present pulley will slip on easily and seat properly. Do not force pulley onto crankshaft, as damage to both will occur voiding the warranty. In the rare case that a pulley is tight clean crank snout (as they can get slightly rusty) with emery cloth until pulley slides on as stated.
- Re-install the original water pump pulley with the factory belt fan.
- Install the new accessory belts in reverse order, see the necessary new belt sizes below.
- Tighten the accessory belts to factory tension specifications and re-install the remaining components in the reverse order.
- Raise the vehicle and remove the safety / jack stands and then lower the vehicle back down.
- The maximum HP gains will occur in 5-7 days of installation, once the computer recalibrates to take advantage of the engines lighter rotational weight.

#### **Crankshaft Pulley Bolt Torque Specification**

- 105-112 ft-lbs. / 142-152 NM / 1260-1344 in-lbs.

**New Belt Sizes** (The belt sizes used may vary slightly. We recommend the use of Gates Brand belts, belt sizing varies slightly among belt manufacturers)

- Alternator and Water Pump – Use Gates K050360 (36 3/4" or 930MM), alternate Gates K050365 (37 1/8" or 945MM).
- Air Conditioning Belt – Use Gates K040330 (33 5/8" or 855MM), alternate gates K040334 (34" or 860MM).
- Power Steering Belt for Non-Hicas Cars – Gates K030335 (34" or 860MM).

\* If a different size belt/s work better on your vehicle please let us know the manufacturer and size of each belt/s used.  
You can contact us by phone or e-mail through our web page. Thank You!

**For technical assistance please contact our technical support line at 631-586-9525 ext. 12  
(Monday-Friday 10AM to 6PM EST)**

**www.unorthodoxracing.com**



## **THE UNORTHODOX PLEDGE**

Unorthodox Racing, Inc. warrants the quality of the products it designs and manufactures to be free of defects in material and workmanship for one year from date of purchase for pulleys, cam gears and aluminum flywheels and 90 days from date of purchase for all stages of clutches. This limited warranty is extended only to the individual purchaser who has purchased our product from an authorized reseller and may not be transferred or assigned. A list of authorized resellers is available on our web site or can be obtained by calling our main offices. This limited warranty applies to any product, which, after careful inspection by Unorthodox Racing Inc., after receipt of the product/s from our authorized reseller, is found to have a defect in either material or workmanship. **UNORTHODOX RACING, INC. PARTS, USED IN COMPETITION OF ANY KIND, SANCTIONED OR UNSANCTIONED, ARE SOLD "AS IS" WITHOUT ANY WARRANTY WHATSOEVER.** Any modifications to the pulley/pulleys will void any and all warranties and will not be exchanged. Before installation, check new car warranty. Unorthodox Racing, Inc. is not responsible for voiding any original manufacturer warranty. All warranty claims must be returned to Unorthodox Racing or your authorized reseller, you must return the product and sales receipt, at your own expense, accompanied by a letter stating the reason for the claim. **PLEASE REFER TO THE PARAGRAPH BELOW FOR THE PROPER RETURN PROCEDURES.** Any claims for pulleys, cam gears or flywheels must be received no later than one year after the date of purchase. Any claims for clutches must be received no later than 90 days from the date of purchase. If all the above procedures are followed, and the product is found to be defective in either material or workmanship, Unorthodox Racing, Inc. shall either repair or replace the product, at its sole discretion, and at its sole cost. This limited warranty does not cover or apply to any personal injury, labor charges, or any other incidental costs or damages caused by the defective product. **THIS LIMITED WARRANTY IS THE ONLY EXPRESS WARRANTY, WHICH APPLIES TO UNORTHODOX RACING PRODUCTS AND IS EXPRESSLY GIVEN IN LIEU OF ANY OTHER WARRANTY EXPRESSED OR IMPLIED, INCLUDING THAT OF MERCHANTABILITY. ANY IMPLIED WARRANTY INCLUDING THAT OF MERCHANTABILITY AND/OR FITNESS FOR A PARTICULAR PURPOSE IS HEREBY LIMITED BY THE SAME TERMS AND TIME LIMITATIONS SET FORTH IN THIS LIMITED EXPRESS WARRANTY AND OTHERWISE EXCLUDED.** You may have rights under either state or federal law, including laws governing warranties, which you should consult. EXCEPT FOR THOSE OBLIGATIONS ASSUMED HEREIN, UNORTHODOX RACING, INC. ASSUMES NO OTHER OBLIGATIONS IN CONNECTION WITH THE SALE OF ITS PRODUCTS.

We sometimes make mistakes, as do our authorized dealers, even customers can order the wrong parts. **DO NOT USE, MODIFY, INSTALL, TRIAL ASSEMBLE, MARK, NICK, DROP, SCRATCH OR BALANCE ANY PART UNTIL YOU FIRST CHECK FOR ANY DAMAGE AND THE PART IS CORRECT FOR YOUR APPLICATION**. Shortages must be reported within five (5) business days of receipt. Damage must be reported immediately, no exceptions. For any shortages or damage please contact Unorthodox Racing Inc or your authorized reseller immediately upon receipt of the shipment. Any parts not purchased directly from Unorthodox Racing Inc, must be processed through the authorized reseller from which you purchased the product. E-Store order return claims must be received within 30 days of the invoice date in order to receive a full credit of the purchase price (less the shipping & handling cost). Any returns after 30 days will be assessed a 30% re-stock fee. If you need to return parts purchased from a dealer you must make your claim for return through that dealer. If you purchased items directly from Unorthodox Racing Inc., discontinued and blow out items are final sale only, please contact our customer service department, they will issue you a "RETURN MERCHANDISE AUTHORIZATION" number (RMA#). For any returns write this RMA number on the outside of the box so that our receiving/shipping department or the authorized resellers receiving/shipping department can expedite the claim. **THE RETURNED PARTS MUST BE IN RESALEABLE CONDITION; THAT IS, IN THE SAME CONDITION YOU RECEIVED THEM. IT IS YOUR RESPONSIBILITY TO CAREFULLY PACKAGE ANY RETURNS TO AVOID SHIPPING DAMAGE, INSURANCE IS HIGHLY RECOMMENDED. CREDIT WILL NOT BE ISSUED FOR DAMAGED GOODS.**

**PLEASE CALL IF YOU HAVE ANY QUESTIONS OR DO NOT UNDERSTAND THIS WARNING!** Refer to our catalog for other terms and conditions. We appreciate your business. The purpose of this warning is to avoid any problems or hard feelings. We will bend over backwards to help you.

**[www.unorthodoxracing.com](http://www.unorthodoxracing.com)**